

Bedrijvenpark Twente 193 NL-702 KG Almelo – The Netherlands

Tel : +31 (0)546 – 572 672 Mail: info@berdal.com

		claration of Performance	
(r	model in accordance with deleg	ated regulation Nr. 574/2014 of the Nr BRD007	e European Commission)
	que identification code of duct-type	FOLIEFOL TOP G, Nr BRD007	
2. Inte	ended use/uses	Reinforced elastic sheets for the application of underlayer for discontinuous roofing	
3. Ma	nufacturer	Berdal Rubber & Plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherlands	
4. Aut	horised representative	Not applicable	
asso	e system or systems for esssing and verifying formance resistance (AVCP)	AVCP 3	
6a. Harmonised standard EN		EN 13859-1	
Not	tified authority	Centrum Stavebniho inzenyrstvi a.s., notification no.: 1390	
7. Dec	clared performance (s)	Essential features:	Performances:
	* =	Fire reaction	Classe F
		Impermeability	Classe W2
		Water vapour transmission rate (Sd)	0,15 m
		Impact load resistance	150/130 N
		Ultimate tensile strength MD/CMD	>220/>230 N/50 mm)
		Tear resistance MD/CMD	>150/>150(%)
		Elongation after artificial ageing MD/CMD	>40 (%)
		Durability with regard to water vapour permeability by ageing	Conform EN 13859-1

The performance of the product identified is in comformity with the set of declared performance/s. This declaration of performance is issued in accordance with (EU) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer. B.M.D. van Kamperdijk, General Manager

Almelo, The Netherlands, 1 March 2018